

Angelchem (Pty) Ltd



PO Box 15005, Farrarmere, 1518 16B Imbali Group, 162 Rangeview Rd, Apex, Benoni Tel: 011 740 7883/26/28/0235 Fax: 011 740 7836
Email: angelchem@polka.co.za Website: www.angelchem.co.za VAT Reg # 4000105603 Co Reg # 2002/016046/07 Export # 21502148
Director: Angelique Stone (Cell 082 462 5144), GM: Elaine Wilken (Cell 083 692 2880) Export & Sales Manager: Willie Horne (Cell 082 455 7684)

Quattro Coat Coal-Tar Distillate Paint Product Data Sheet

Application

Quattro Coat is a solvent-based coal-tar distillate paint. It is suitable for painting fences, droppers & steel posts. Quattro Coat can also be used for wooden tar poles, waterproofing, wooden under-flooring and general paint work on unprepared material. Simply ensure that the surface is clean and oil-free and apply.

Application can be done by either dipping or painting onto the surface with a roller or brush. One to two coats may be applied according to your needs. Quattro coat will prevent deterioration by way of rust and wood rot of the covered surface and protect against wind and weather.

Quattro Coat is not to be used on rusted surfaces without pre-cleaning as this is not a rust converter.

Safety and Handling

Avoid contact with skin, eyes and clothing. Avoid breathing vapour or fumes. When using do not eat, drink or smoke. Keep away from open flames or sparks.

Precautions:

Quattro Coat is to be stored in tightly sealed containers. Overheating and pressure build-up must be avoided. Electrical equipment must be flameproof and earthed.

Storage:

Keep away from sources of ignition. Use lowest practical storage temperatures to minimise fume generation.

Physical Properties

Appearance:	Thick Black Liquid
Flammability:	Flammable
Density:	1.153
Flash point:	55°C min

Packaging:

1Lt, 5Lt, 25Lt and 200Lt tins and steel drums.

